















KFG Gages ● Uniaxial 60Ω

Pattern	Leadwire Cable – Type and Shape	Operating Temp. Range	Leadwire Length	Model	
KFG-5-60-C1-11 16 23 27	Vinyl-coated flat 3-wire cable L-7 (L-10 for 6m or longer)	-10 to 80°C	1m	KFG-5-60-C1-11 L1M3R	
			3m	KFG-5-60-C1-11 L3M3R	
			5m	KFG-5-60-C1-11 L5M3R	
		Vinyl-coated flat 2-wire cable L-6 (L-9 for 6m or longer)	-10 to 80°C	1m	KFG-5-60-C1-11 L1M2R
				3m	KFG-5-60-C1-11 L3M2R
				5m	KFG-5-60-C1-11 L5M2R
		Middle-temperature 3-wire cable L-12	-100 to 150°C	1m	KFG-5-60-C1-11 R1M3
				3m	KFG-5-60-C1-11 R3M3
				5m	KFG-5-60-C1-11 R5M3
		Middle-temperature 2-wire cable L-11	-100 to 150°C	1m	KFG-5-60-C1-11 R1M2
				3m	KFG-5-60-C1-11 R3M2
				5m	KFG-5-60-C1-11 R5M2
		3 polyester-coated copper wires	-196 to 150°C	30cm	KFG-5-60-C1-11 N30C3
				50cm	KFG-5-60-C1-11 N50C3
				1m	KFG-5-60-C1-11 N1M3
	2 polyester-coated copper wires	-196 to 150°C	30cm	KFG-5-60-C1-11 N30C2	
			50cm	KFG-5-60-C1-11 N50C2	
			1m	KFG-5-60-C1-11 N1M2	
	Silver-clad copper wires	-196 to 150°C	25mm	KFG-5-60-C1-11	
KFG-2-60-C1-11 16 23 27	Vinyl-coated flat 3-wire cable L-7 (L-10 for 6m or longer)	-10 to 80°C	1m	KFG-2-60-C1-11 L1M3R	
			3m	KFG-2-60-C1-11 L3M3R	
			5m	KFG-2-60-C1-11 L5M3R	
		Vinyl-coated flat 2-wire cable L-6 (L-9 for 6m or longer)	-10 to 80°C	1m	KFG-2-60-C1-11 L1M2R
				3m	KFG-2-60-C1-11 L3M2R
				5m	KFG-2-60-C1-11 L5M2R
		Middle-temperature 3-wire cable L-12	-100 to 150°C	1m	KFG-2-60-C1-11 R1M3
				3m	KFG-2-60-C1-11 R3M3
				5m	KFG-2-60-C1-11 R5M3
		Middle-temperature 2-wire cable L-11	-100 to 150°C	1m	KFG-2-60-C1-11 R1M2
				3m	KFG-2-60-C1-11 R3M2
				5m	KFG-2-60-C1-11 R5M2
		3 polyester-coated copper wires	-196 to 150°C	30cm	KFG-2-60-C1-11 N30C3
				50cm	KFG-2-60-C1-11 N50C3
				1m	KFG-2-60-C1-11 N1M3
	2 polyester-coated copper wires	-196 to 150°C	30cm	KFG-2-60-C1-11 N30C2	
			50cm	KFG-2-60-C1-11 N50C2	
			1m	KFG-2-60-C1-11 N1M2	
	Silver-clad copper wires	-196 to 150°C	25mm	KFG-2-60-C1-11	















Uniaxial

- Base Size 10 x 3.4 mm
- Gage Length 5 mm
- Gage Resistance 60Ω
- Pieces per Pack 10

Uniaxial

- Base Size 7.2 x 3.7mm
- Gage Length 2 mm
- Gage Resistance 60Ω
- Pieces per Pack 10

KFG Gages ● Uniaxial 350Ω

Pattern	Leadwire Cable - Type and Shape	Operating Temp. Range	Leadwire Length	Model
KFG-5-350-C1-11 16 23 27	 Vinyl-coated flat 3-wire cable L-7 (L-10 for 6m or longer)	-10 to 80°C	1m	KFG-5-350-C1-11 L1M3R
			3m	KFG-5-350-C1-11 L3M3R
			5m	KFG-5-350-C1-11 L5M3R
	 Vinyl-coated flat 2-wire cable L-6 (L-9 for 6m or longer)	-10 to 80°C	1m	KFG-5-350-C1-11 L1M2R
			3m	KFG-5-350-C1-11 L3M2R
			5m	KFG-5-350-C1-11 L5M2R
	 Middle-temperature 3-wire cable L-12	-100 to 150°C	1m	KFG-5-350-C1-11 R1M3
			3m	KFG-5-350-C1-11 R3M3
			5m	KFG-5-350-C1-11 R5M3
	 Middle-temperature 2-wire cable L-11	-100 to 150°C	1m	KFG-5-350-C1-11 R1M2
			3m	KFG-5-350-C1-11 R3M2
			5m	KFG-5-350-C1-11 R5M2
	 3 polyester-coated copper wires	-196 to 150°C	30cm	KFG-5-350-C1-11 N30C3
			50cm	KFG-5-350-C1-11 N50C3
			1m	KFG-5-350-C1-11 N1M3
 2 polyester-coated copper wires	-196 to 150°C	30cm	KFG-5-350-C1-11 N30C2	
		50cm	KFG-5-350-C1-11 N50C2	
		1m	KFG-5-350-C1-11 N1M2	
 Silver-clad copper wires	-196 to 150°C	25mm	KFG-5-350-C1-11	
KFG-3-350-C1-11 16 23 27	 Vinyl-coated flat 3-wire cable L-7 (L-10 for 6m or longer)	-10 to 80°C	1m	KFG-3-350-C1-11 L1M3R
			3m	KFG-3-350-C1-11 L3M3R
			5m	KFG-3-350-C1-11 L5M3R
	 Vinyl-coated flat 2-wire cable L-6 (L-9 for 6m or longer)	-10 to 80°C	1m	KFG-3-350-C1-11 L1M2R
			3m	KFG-3-350-C1-11 L3M2R
			5m	KFG-3-350-C1-11 L5M2R
	 Middle-temperature 3-wire cable L-12	-100 to 150°C	1m	KFG-3-350-C1-11 R1M3
			3m	KFG-3-350-C1-11 R3M3
			5m	KFG-3-350-C1-11 R5M3
	 Middle-temperature 2-wire cable L-11	-100 to 150°C	1m	KFG-3-350-C1-11 R1M2
			3m	KFG-3-350-C1-11 R3M2
			5m	KFG-3-350-C1-11 R5M2
	 3 polyester-coated copper wires	-196 to 150°C	30cm	KFG-3-350-C1-11 N30C3
			50cm	KFG-3-350-C1-11 N50C3
			1m	KFG-3-350-C1-11 N1M3
 2 polyester-coated copper wires	-196 to 150°C	30cm	KFG-3-350-C1-11 N30C2	
		50cm	KFG-3-350-C1-11 N50C2	
		1m	KFG-3-350-C1-11 N1M2	
 Silver-clad copper wires	-196 to 150°C	25mm	KFG-3-350-C1-11	












Uniaxial

- Base Size 9.4 x 4.2 mm
- Gage Length 5 mm
- Gage Resistance 350Ω
- Pieces per Pack 10

Uniaxial

- Base Size 7.4 x 4.2 mm
- Gage Length 3 mm
- Gage Resistance 350Ω
- Pieces per Pack 10

KFG Gages ● Uniaxial 350Ω

Pattern	Leadwire Cable – Type and Shape	Operating Temp. Range	Leadwire Length	Model		
KFG-2-350-C1-11 16 23 27	Vinyl-coated flat 3-wire cable L-7 (L-10 for 6m or longer)	-10 to 80°C	1m	KFG-2-350-C1-11 L1M3R		
			3m	KFG-2-350-C1-11 L3M3R		
			5m	KFG-2-350-C1-11 L5M3R		
		Vinyl-coated flat 2-wire cable L-6 (L-9 for 6m or longer)	-10 to 80°C	1m	KFG-2-350-C1-11 L1M2R	
				3m	KFG-2-350-C1-11 L3M2R	
				5m	KFG-2-350-C1-11 L5M2R	
		Middle-temperature 3-wire cable L-12	-100 to 150°C	1m	KFG-2-350-C1-11 R1M3	
				3m	KFG-2-350-C1-11 R3M3	
				5m	KFG-2-350-C1-11 R5M3	
		Middle-temperature 2-wire cable L-11	-100 to 150°C	1m	KFG-2-350-C1-11 R1M2	
				3m	KFG-2-350-C1-11 R3M2	
				5m	KFG-2-350-C1-11 R5M2	
		3 polyester-coated copper wires	-196 to 150°C	30cm	KFG-2-350-C1-11 N30C3	
				50cm	KFG-2-350-C1-11 N50C3	
		1m		KFG-2-350-C1-11 N1M3		
	2 polyester-coated copper wires	-196 to 150°C	30cm	KFG-2-350-C1-11 N30C2		
			50cm	KFG-2-350-C1-11 N50C2		
			1m	KFG-2-350-C1-11 N1M2		
Uniaxial ● Base Size 6.3 x 4.2 mm ● Gage Length 2 mm ● Gage Resistance 350Ω ● Pieces per Pack 10	Silver-clad copper wires	-196 to 150°C	25mm	KFG-2-350-C1-11		
	KFG-1-350-C1-11 16 23 27	Vinyl-coated flat 3-wire cable L-7 (L-10 for 6m or longer)	-10 to 80°C	1m	KFG-1-350-C1-11 L1M3R	
				3m	KFG-1-350-C1-11 L3M3R	
				5m	KFG-1-350-C1-11 L5M3R	
			Vinyl-coated flat 2-wire cable L-6 (L-9 for 6m or longer)	-10 to 80°C	1m	KFG-1-350-C1-11 L1M2R
					3m	KFG-1-350-C1-11 L3M2R
					5m	KFG-1-350-C1-11 L5M2R
			Middle-temperature 3-wire cable L-12	-100 to 150°C	1m	KFG-1-350-C1-11 R1M3
					3m	KFG-1-350-C1-11 R3M3
					5m	KFG-1-350-C1-11 R5M3
			Middle-temperature 2-wire cable L-11	-100 to 150°C	1m	KFG-1-350-C1-11 R1M2
					3m	KFG-1-350-C1-11 R3M2
					5m	KFG-1-350-C1-11 R5M2
			2 polyester-coated copper wires	-196 to 150°C	30cm	KFG-1-350-C1-11 N30C2
			50cm		KFG-1-350-C1-11 N50C2	
	1m		KFG-1-350-C1-11 N1M2			
Uniaxial ● Base Size 4.8 x 3.4 mm ● Gage Length 1 mm ● Gage Resistance 350Ω ● Pieces per Pack 10	Silver-clad copper wires	-196 to 150°C	25mm	KFG-1-350-C1-11		